

Product Availability

**We Have the V10 and V20
Series Vane Pumps!**

Interchange with the Vickers series



See the attached Product Sheet
for details and ordering information.



And, remember, in most cases, we ship out orders the same day we receive them.
In fact, over 95% of orders go out the same day!

Wishing you the best,

Jim Cubberly, Product Manager
jim@northmanfp.com

V10 & V20 Vane Pumps



Fixed Displacement Vane Pump

1 GPM to 13 GPM Flow at 1200 RPM Rating

3.6 GPM to 25.9 GPM Flow at Max RPM Rating

Up to 2500 Max PSI

V10 & V20 Single Vane Pumps Ordering Information

V10 - 1 P 5 S - 1 C 30 L

Shaft Rotation – Viewed from Shaft End

L = Left Hand (Counterclockwise)

Blank = Right Hand (Clockwise)

Design No.

Position of Outlet Port – Viewed from Cover End

A = Opposite Inlet

B = 90° CCW from Inlet

C = Inline with Inlet

D = 90° CW from Inlet

Shafts

1 = Straight Keyed

11 = Splined

Outlet Port Connection

P = NPT: 1/2" for V10

3/4" for V20

S = St. Thd: .750-16 for V10

1.0625-12 for V20

Flow Capacity at 1200 RPM & 100 PSI

V10: 1, 2, 3, 4, 5, 6, 7 GPM

V20: 6, 7, 8, 9, 11, 12, 13 GPM

Inlet Port Connection

P = NPT: 1" for V10

1-1/4" for V20

S = St. Thd: 1.3125-12 for V10

1.625-12 for V20

Mounting

1 = 2-Bolt Flange, 3.25" Pilot – Standard

2 = 2-Bolt Flange, 4.00" Pilot – Optional

Series

V10 or V20

TYPE	FLOW (GPM @ 1200 RPM and 100 PSI)	MAX RPM	MAX PSI	GPM FLOW AT MAX SPEED
V10	1	4800	2500	3.6
	2	4500	2500	7.3
	3	4000	2500	9.4
	4	3400	2500	10.9
	5	3200	2500	12.8
	6	3000	2200	14.6
	7	2800	2000	16.0
V20	6	3400	2500	16.1
	7	3000	2500	16.7
	8	2800	2500	17.7
	9	2800	2500	19.8
	11	2500	2500	22.9
	12	2400	2200	23.0
13	2400	2200	25.9	